

Product name	Type of screwdriver			Tightening torque	Cable stripping length	Copper cables capability					Copper cables capability	Multi cables configuration			
								Rigid			Flexible with ferrule				
								Mini - Maxi			Mini - Maxi				
RCCB															
GFP UL1053	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 1.5 to 10 mm²	2 x 1.5 to 10 mm²	2 x 1.5 to 10 mm²		
RCCB ID - IEC/EN 61008-1	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 1.5 to 10 mm²	2 x 1.5 to 10 mm²	2 x 1.5 to 10 mm²		
RCCB-ID 125 A	PZ2	6.5 mm	-	3 N.m	11 mm	1.5 mm² to 50 mm²	1.5 mm² to 35 mm²			1.5 mm² to 35 mm²	2 x 1.5 to 16 mm²	2 x 1.5 to 16 mm²	2 x 1.5 to 16 mm²		
iID double terminals Front terminal	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 4 mm² / 2 x 6 mm²	2 x 4 mm² / 2 x 6 mm²	2 x 4 mm² / 2 x 6 mm²		
iID double terminals Back terminal	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 25 mm²	1 mm² to 16 mm²			1 mm² to 16 mm²	2 x 4 mm² / 2 x 6 mm²	2 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm²		
iID single terminal	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
iID B Type Front terminal	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 4 mm² / 2 x 6 mm²	2 x 4 mm² / 2 x 6 mm²	2 x 4 mm² / 2 x 6 mm²		
iID B Type Back terminal	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 25 mm²	1 mm² to 16 mm²			1 mm² to 16 mm²	2 x 4 mm² / 2 x 6 mm²	2 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm²		
iID K	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
ID K Biconnect	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
iID40 Top terminal	PZ2	5.5 mm	-	2 N.m	14 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
iID40 Bottom terminal	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
RCD Add-On															
Vigi C60	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 1.5 to 10 mm²	2 x 1.5 to 10 mm²	2 x 1.5 to 10 mm²		
Vigi N40	PZ2	5.5 mm	-	2 N.m	13 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
Vigi iC40	PZ2	5.5 mm	-	2 N.m	14 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
Vigi iICG40 Top terminal	PZ2	5.5 mm	-	2 N.m	14 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
Vigi iICG40 Bottom terminal	PZ2	6.5 mm	-	2 N.m	14 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
Vigi iC60 25 A	PZ2	6.5 mm	-	2 N.m	14 mm	1 mm² to 25 mm²	1 mm² to 16 mm²			1 mm² to 16 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
Vigi iC60 40 A & 63 A	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
Vigi iC60 25 A for iC60 double terminal	PZ2	6.5 mm	-	2 N.m	14 mm	1 mm² to 25 mm²	1 mm² to 16 mm²			1 mm² to 16 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
Vigi iC60 63 A for iC60 double terminal	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
Vigi C120	PZ2	6.5 mm	-	3.5 N.m	15 mm	1 mm² to 50 mm²	1 mm² to 35 mm²			1 mm² to 35 mm²	3 x 10 mm² / 2 x 16 mm²	3 x 10 mm² / 2 x 16 mm²	3 x 10 mm² / 2 x 16 mm²		
Vigi C120 63 A	PZ2	6.5 mm	-	3.5 N.m	20 mm	1.5 mm² to 50 mm²	1.5 mm² to 35 mm²			1.5 mm² to 35 mm²	-	-	-		
Vigi NG125 125 A	-	-	4 mm	6 N.m	20 mm	16 mm² to 70 mm²	10 mm² to 50 mm²			10 mm² to 50 mm²	-	-	-		
Vigi NG125 Pre-alarm terminals	PZ1	5 mm	-	1 N.m	-	2.5 mm² to 2.5 mm²	1.5 mm² to 1.5 mm²			1.5 mm² to 1.5 mm²	2 x 2.5 mm²	2 x 1.5 mm²	2 x 1.5 mm²		
RCBO															
N40 Vigi	PZ2	5.5 mm	-	2 N.m	13 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
iDPN Vigi	PZ2	5.5 mm	-	2 N.m	15 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
iCV40, iCV40N, iCV40H	PZ2	5.5 mm	-	2 N.m	13 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
DPNa Vigi, DPN N Vigi	PZ2	5.5 mm	-	2 N.m	15 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
DPN Vigi K Neutral terminal	PZ2	5.5 mm	-	2 N.m	15 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
DPN Vigi K Phase terminal	PZ2	6.5 mm	-	2 N.m	15 mm	1 mm² to 25 mm²	1 mm² to 16 mm²			1 mm² to 16 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		
REDs, REDtest Neutral & Phase terminals	PZ2	5.5 mm	-	2 N.m	12 mm	1 mm² to 35 mm²	1 mm² to 35 mm²			1 mm² to 35 mm²	-	-	-		
REDs, REDtest Auxiliary terminals	-	-	-	0.4 N.m	9 mm	1 mm² to 2.5 mm²	1 mm² to 2.5 mm²			1 mm² to 2.5 mm²	-	-	-		
DPNa Vigi, DPN N Vigi	PZ2	5.5 mm	-	2 N.m	15 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²		

Product name	Type of screwdriver			Tightening torque	Cable stripping length	Copper cables capability				Copper cables capability	Multi cables configuration		
						Rigid	Flexible with ferrule			Flexible without ferrule	Rigid	Flexible with Single ferrule	Flexible without ferrule
	Pz	Flat	Hc										
Fuse Holder													
STI Fuse Holder	PZ2	5.5 mm	-	2 N.m	12 mm	0.75 mm² to 10 mm²	0.5 mm² to 6 mm²			1 mm² to 6 mm²	2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 4 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 4 mm²	2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 4 mm²
D01 Fuse Holder	PZ2	5.5 mm	-	2 N.m	14 mm	1.5 mm² to 25 mm²	1.5 mm² to 16 mm²			1.5 mm² to 16 mm²	-	-	-
D02 Fuse Holder	PZ2	5.5 mm	-	3 N.m	14 mm	1.5 mm² to 35 mm²	1.5 mm² to 25 mm²			1.5 mm² to 25 mm²	-	-	-
SBI Fuse Holder 14 x 51 mm	PZ2	5 mm	-	3.5 N.m	10 mm	2.5 mm² to 25 mm²	2.5 mm² to 25 mm²			2.5 mm² to 25 mm²	-	-	-
SBI Fuse Holder 22 x 58 mm	PZ2	6 mm	-	3.5 N.m	12 mm	2.5 mm² to 35 mm²	2.5 mm² to 35 mm²			2.5 mm² to 35 mm²	-	-	-
AFDD													
iARC	PZ2	5.5 mm	-	2 N.m	14 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²
iDPN N Arc	PZ2	5.5 mm	-	2 N.m	14 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²
iARC DPNN	PZ2	5.5 mm	-	2 N.m	14 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²
iDPN Vigi Arc ELE	PZ2	5.5 mm	-	2 N.m	14 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²
iC40 ARC	PZ2	5.5 mm	-	2 N.m	14 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²
iCV40 ARC	PZ2	5.5 mm	-	2 N.m	14 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²
iDPN VigiARC	PZ2	5.5 mm	-	2 N.m	14 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²
iDPN ARC	PZ2	5.5 mm	-	2 N.m	14 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²
SPD													
iPRF1 12.5r	PZ2	6.5 mm	-	2 N.m	-	10 mm² to 25 mm²	10 mm² to 16 mm²			10 mm² to 16 mm²	-	-	-
PRD1 35r	PZ2	6.5 mm	-	4.5 N.m	-	16 mm² to 35 mm²	16 mm² to 25 mm²			16 mm² to 25 mm²	-	-	-
PRD1 25r	PZ2	6.5 mm	-	4.5 N.m	-	16 mm² to 35 mm²	16 mm² to 25 mm²			16 mm² to 25 mm²	-	-	-
PRD1 Master	PZ2	6.5 mm	-	4.5 N.m	-	16 mm² to 35 mm²	16 mm² to 25 mm²			16 mm² to 25 mm²	-	-	-
iPF	PZ2	6.5 mm	-	2.5 N.m	11 mm	2.5 mm² to 35 mm²	2.5 mm² to 25 mm²			2.5 mm² to 25 mm²	-	-	-
iPF K	PZ2	6.5 mm	-	2.5 N.m	11 mm	2.5 mm² to 35 mm²	2.5 mm² to 25 mm²			2.5 mm² to 25 mm²	-	-	-
iPRD	PZ2	6.5 mm	-	2.5 N.m	14 mm	2.5 mm² to 35 mm²	2.5 mm² to 25 mm²			2.5 mm² to 25 mm²	-	-	-
iQuick PRD Ph/N	PZ2	6.5 mm	-	2.5 N.m	12 mm	2.5 mm² to 35 mm²	2.5 mm² to 25 mm²			2.5 mm² to 25 mm²	-	-	-
iQuirk PRD Earth	PZ2	6.5 mm	-	2.5 N.m	11 mm	10 mm² to 25 mm²	10 mm² to 25 mm²			10 mm² to 25 mm²	-	-	-
iQuick PF Ph/N	PZ2	5.5 mm	-	2 N.m	13 mm	1 mm² to 16 mm²	1 mm² to 10 mm²			1 mm² to 10 mm²	-	-	-
iQuick PF Earth	PZ2	5.5 mm	-	2 N.m	-	10 mm² to 25 mm²	10 mm² to 25 mm²			10 mm² to 25 mm²	-	-	-
iPRC	PZ1	3 mm	-	0.8 N.m	8 mm	0.2 mm² to 4 mm²	0.2 mm² to 2.5 mm²			0.2 mm² to 2.5 mm²	-	-	-
iPRI	PZ1	3 mm	-	0.8 N.m	8 mm	0.2 mm² to 4 mm²	0.2 mm² to 2.5 mm²			0.2 mm² to 2.5 mm²	-	-	-
iPRD-DC	PZ2	6.5 mm	-	2.5 N.m	14 mm	2.5 mm² to 35 mm²	2.5 mm² to 25 mm²			2.5 mm² to 25 mm²	-	-	-
iPRD PV-DC	PZ2	6.5 mm	-	2.5 N.m	14 mm	2.5 mm² to 35 mm²	2.5 mm² to 25 mm²			2.5 mm² to 25 mm²	-	-	-
Switch													
iSW	PZ2	6.5 mm	-	3.5 N.m	14 mm	1.5 mm² to 50 mm²	1.5 mm² to 35 mm²			1.5 mm² to 35 mm²	-	-	-
SW Biconnect	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²
iSW-NA	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²
NG125NA 63 A	PZ2	6.5 mm	-	3.5 N.m	20 mm	1.5 mm² to 50 mm²	1.5 mm² to 35 mm²			1.5 mm² to 35 mm²	3 x 10 mm² / 2 x 16 mm²	3 x 10 mm² / 2 x 16 mm²	3 x 10 mm² / 2 x 16 mm²
NG125NA > 63 A	-	-	4 mm	6 N.m	20 mm	16 mm² to 70 mm²	10 mm² to 50 mm²			10 mm² to 50 mm²	3 x 10 mm² / 2 x 16 mm² / 2 x 35 mm²	3 x 10 mm² / 2 x 16 mm² / 2 x 25 mm²	3 x 10 mm² / 2 x 16 mm² / 2 x 25 mm²
Auxiliaries													
iMN, iMNs, iMNx ,iMSU, iMx , iMx+OF	PZ1	4 mm	-	1 N.m	10 mm	1 mm² to 6 mm²	1 mm² to 4 mm²			1 mm² to 4 mm²	2 x 2.5 mm² / 2 x 1.5 mm²	2 x 2.5 mm² / 2 x 1.5 mm²	2 x 2.5 mm² / 2 x 1.5 mm²
MN, MNs, MNx , Mx , Mx+OF	PZ1	4 mm	-	1 N.m	9 mm	1 mm² to 6 mm²	1 mm² to 4 mm²			1 mm² to 4 mm²	2 x 2.5 mm² / 2 x 1.5 mm²	2 x 2.5 mm² / 2 x 1.5 mm²	2 x 2.5 mm² / 2 x 1.5 mm²
iOF, iSD, iOF/SD+OF	PZ1	4 mm	-	1 N.m	10 mm	1 mm² to 4 mm²	1 mm² to 2.5 mm²			1 mm² to 2.5 mm²	2 x 2.5 mm² / 2 x 1.5 mm²	2 x 1.5 mm²	2 x 1.5 mm²
OF, SD, OF+SD/OF	PZ1	4 mm	-	1 N.m	10 mm	1 mm² to 4 mm²	1 mm² to 2.5 mm²			1 mm² to 2.5 mm²	2 x 2.5 mm² / 2 x 1.5 mm²	2 x 1.5 mm²	2 x 1.5 mm²
MN NG125, MNx NG125, Mx+OF NG125	PZ1	5 mm	-	1 N.m	10 mm	1 mm² to 2.5 mm²	1 mm² to 1.5 mm²			1 mm² to 1.5 mm²	2 x 2.5 mm² / 2 x 1.5 mm²	2 x 1.5 mm²	2 x 1.5 mm²
OF+OF NG125, OF+SD NG125	PZ1	5 mm	-	1 N.m	10 mm	1 mm² to 2.5 mm²	1 mm² to 1.5 mm²			1 mm² to 1.5 mm²	2 x 2.5 mm² / 2 x 1.5 mm²	2 x 1.5 mm²	2 x 1.5 mm²
MXV Vigi NG215, SDV Vigi NG125	PZ1	5 mm	-	1 N.m	10 mm	1 mm² to 2.5 mm²	1 mm² to 1.5 mm²			1 mm² to 1.5 mm²	2 x 2.5 mm² / 2 x 1.5 mm²	2 x 1.5 mm²	2 x 1.5 mm²

Product name	Type of screwdriver			Tightening torque	Cable stripping length	Copper cables capability				Copper cables capability	Multi cables configuration			
						Rigid	Flexible with ferrule				Flexible without ferrule			
	Pz	Flat	Hc			Mini - Maxi	Mini - Maxi			Mini - Maxi				
RCA														
RCA, ARA Power supply N/P and Inputs Y1/Y2	PZ1	3.5 mm	-	1 N.m	10 mm	0.5 mm² to 10 mm²	0.5 mm² to 4 mm²			0.5 mm² to 6 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	
RCA, ARA Outputs OF	-	3.5 mm	-	0.7 N.m	8 mm	0.5 mm² to 2.5 mm²	0.5 mm² to 1.5 mm²			0.5 mm² to 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm²	
-														
iPB	PZ1	4 mm	-	1 N.m	9 mm	0.5 mm² to 2.5 mm²	0.5 mm² to 2.5 mm²			0.5 mm² to 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	
iSSW	PZ1	4 mm	-	1 N.m	9 mm	0.5 mm² to 2.5 mm²	0.5 mm² to 2.5 mm²			0.5 mm² to 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	
iCMB	-	-	-	0.35 N.m	-	-	-			-	-	-	-	
Reflex iC60N, iC60H Power ≤ 25 A	PZ2	6.5 mm	-	2 N.m	14 mm	1 mm² to 25 mm²	1 mm² to 16 mm²			1 mm² to 16 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	
Reflex iC60N, iC60H Power > 25 A	PZ2	6.5 mm	-	3.5 N.m	14 mm	1 mm² to 35 mm²	1 mm² to 25 mm²			1 mm² to 25 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	2 x 4 mm² / 2 x 6 mm² / 2 x 1.5 mm² + 1 x 2.5 mm²	
Reflex iC60N, iC60H Power supply N/P and Inputs Y1/Y2	PZ1	3.5 mm	-	1 N.m	10 mm	1 mm² to 10 mm²	1 mm² to 4 mm²			1 mm² to 6 mm²	-	-	-	
Reflex iC60N, iC60H Outputs OF	-	3.5 mm	-	0.7 N.m	8 mm	1 mm² to 2.5 mm²	1 mm² to 1.5 mm²			1 mm² to 2.5 mm²	-	-	-	
CT														
iCT ≤ 25 A Control	PZ1	4 mm	-	0.8 N.m	9 mm	1.5 mm² to 2.5 mm²	1.5 mm² to 2.5 mm²			1.5 mm² to 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	
iCT ≤ 25 A Power	PZ1	4 mm	-	0.8 N.m	9 mm	1.5 mm² to 6 mm²	1.5 mm² to 4 mm²			1.5 mm² to 4 mm²	-	-	-	
iCT 40-63 A Control	PZ1	4 mm	-	0.8 N.m	9 mm	1.5 mm² to 2.5 mm²	1.5 mm² to 2.5 mm²			1.5 mm² to 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	
iCT 40-63 A Power	PZ2	6 mm	-	3.5 N.m	14 mm	6 mm² to 25 mm²	6 mm² to 16 mm²			6 mm² to 16 mm²	-	-	-	
iCT 100 A Control	PZ1	4 mm	-	0.8 N.m	9 mm	1.5 mm² to 2.5 mm²	1.5 mm² to 2.5 mm²			1.5 mm² to 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	
iCT 100 A Power	PZ2	6 mm	-	3.5 N.m	14 mm	6 mm² to 35 mm²	6 mm² to 25 mm²			6 mm² to 25 mm²	-	-	-	
CT40 Control	PZ1	4 mm	-	0.8 N.m	9 mm	1.5 mm² to 2.5 mm²	1.5 mm² to 2.5 mm²			1.5 mm² to 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	
CT40 Power	PZ1	4 mm	-	0.8 N.m	9 mm	1.5 mm² to 6 mm²	1.5 mm² to 4 mm²			1.5 mm² to 4 mm²	-	-	-	
iCT+	PZ1	3.5 mm	-	1 N.m	10 mm	1 mm² to 4 mm²	1 mm² to 2.5 mm²			1 mm² to 4 mm²	2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1 mm² / 2 x 1.5 mm²	2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	
CT auxiliaries														
iACT24	PZ1	3.5 mm	-	1 N.m	9 mm	0.5 mm² to 10 mm²	0.5 mm² to 4 mm²			0.5 mm² to 6 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	
iACTs, iACTp, iACTc, iATEt	PZ1	4 mm	-	0.8 N.m	9 mm	1.5 mm² to 2.5 mm²	1.5 mm² to 2.5 mm²			1.5 mm² to 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1.5 mm² / 2 x 2.5 mm²	
TL auxiliaries														
iTL, iTLl, iTLc, iTLm, iTLs, iETL 16 A Control	PZ1	3.5 mm	-	1 N.m	11 mm	1 mm² to 4 mm²	1 mm² to 4 mm²			1 mm² to 4 mm²	-	-	-	
iTL, iTLl, iTLc, iTLm, iTLs, iETL 16 A Power	PZ1	3.5 mm	-	1 N.m	11 mm	1.5 mm² to 4 mm²	1.5 mm² to 4 mm²			1.5 mm² to 4 mm²	-	-	-	
iTL, iETL 32 A Control	PZ1	3.5 mm	-	1 N.m	11 mm	1 mm² to 4 mm²	1 mm² to 4 mm²			1 mm² to 4 mm²	-	-	-	
iTL, iETL 32 A Power	PZ1	3.5 mm	-	1.2 N.m	11 mm	1.5 mm² to 10 mm²	1.5 mm² to 10 mm²			1.5 mm² to 10 mm²	-	-	-	
iATL24	PZ1	3.5 mm	-	1 N.m	9 mm	0.5 mm² to 10 mm²	0.5 mm² to 4 mm²			0.5 mm² to 6 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	
TL40 Control	PZ1	3.5 mm	-	1 N.m	9 mm	0.5 mm² to 1.5 mm²	0.5 mm² to 1.5 mm²			0.5 mm² to 1.5 mm²	-	-	-	
TL40 Power	PZ1	3.5 mm	-	1 N.m	9 mm	1 mm² to 4 mm²	1 mm² to 4 mm²			1 mm² to 4 mm²	2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	
iTL+	PZ1	3.5 mm	-	1 N.m	10 mm	1 mm² to 4 mm²	1 mm² to 2.5 mm²			1 mm² to 4 mm²	2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 1 mm² / 2 x 1.5 mm²	2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	
iATLs, iATLc, iATLc+s, iATLc+c, iATLm, iATEt, iATL4, iATLz	PZ1	3.5 mm	-	1 N.m	11 mm	1 mm² to 4 mm²	1 mm² to 4 mm²			1 mm² to 4 mm²	-	-	-	
Indicator														
iIL	PZ1	4 mm	-	1 N.m	9 mm	0.5 mm² to 2.5 mm²	0.5 mm² to 2.5 mm²			0.5 mm² to 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	2 x 0.5 mm² / 2 x 0.75 mm² / 2 x 1 mm² / 2 x 1.5 mm² / 2 x 2.5 mm²	
Bell & Buzzer														
ISO, iRO	PZ1	3.5 mm	-	1.3 N.m	12 mm	1 mm² to 4 mm²	1 mm² to 4 mm²			1 mm² to 4 mm²	-	-	-	
Transformer														
iTR	PZ1	6 mm	-	0.5 N.m	6 mm	1 mm² to 2.5 mm²	1 mm² to 2.5 mm²			1 mm² to 2.5 mm²	-	-	-	
Load shedder														
DSE1	PZ2	5.5 mm	-	1.2 N.m	12 mm	1 mm² to 6 mm²	1 mm² to 6 mm²			1 mm² to 6 mm²	-	-	-	
CDS, CDS <i>c</i> Priority circuit	-	5.5 mm	-	3.5 N.m	12 mm/ 13 mm	10 mm² to 50 mm²	10 mm² to 35 mm²			10 mm² to 35 mm²	-	-	-	
CDS, CDS <i>c</i> Non-priority circuit	-	5.5 mm	-	2 N.m	12 mm/ 13 mm	2.5 mm² to 10 mm²	2.5 mm² to 10 mm²			2.5 mm² to 10 mm²	-	-	-	

Product name	Type of screwdriver			Tightening torque	Cable stripping length	Copper cables capability				Copper cables capability	Multi cables configuration			
						Rigid	Flexible with ferrule				Rigid		Flexible with Single ferrule	Flexible without ferrule
						Mini - Maxi	Mini - Maxi							
	Pz	Flat	Hc											
Power socket														
IPC 16 A	PZ2	4 mm	-	1.2 N.m	12 mm	1 mm² to 10 mm²	1 mm² to 6 mm²			1 mm² to 6 mm²	-	-	-	-
Twilight switch														
IC100, IC2000P+	PZ1	5 mm	-	1.2 N.m	8 mm	1 mm² to 6 mm²	1 mm² to 6 mm²			1 mm² to 6 mm²	-	-	-	-
Timer														
MIN, MINs, MINp, MINT	PZ1	5 mm	-	1.2 N.m	8 mm	1 mm² to 6 mm²	1 mm² to 6 mm²			1 mm² to 6 mm²	-	-	-	-
Dimmer														
STD and SCU Top connection	-	3 mm	-	0.5 N.m	8 mm	1 mm² to 4 mm²	1 mm² to 4 mm²			1 mm² to 4 mm²	-	-	-	-
STD and SCU Bottom connection	-	3 mm	-	0.5 N.m	8 mm	1 mm² to 2.5 mm²	1 mm² to 2.5 mm²			1 mm² to 2.5 mm²	-	-	-	-
STD400LED, STD400LED+	-	3 mm	-	0.5 N.m	8 mm	1 mm² to 2.5 mm²	1 mm² to 2.5 mm²			1 mm² to 2.5 mm²	-	-	-	-



1.0	18/01/2021	Creation	Sonovision
Indice	Date	Modification	Name