



Alarm Equipment

- | | | | |
|---|--|---|--|
|  ESI-10, Ancillary Base Sounder (Detector Remote Output Controlled) 85dBA FFS06728010 |  ESI-50, Red Open-Area Sounder, 100 dBA FFS06728050 |  Configurable Open Area Sounder Beacon with Base FFS06728118 |  MBA-6, Fire Bell Outdoor FFS06431505 |
|  ESI-30, Addressable Integrated Base Sounder, 55 - 91 dBA FFS06728030 |  ESI-60, Addressable Sounder-Beacon Base FFS06728060 |  C-C Ceiling Visual Alarm Device 8m Red, Loop Powered FFS06728126 |  BBX-4, Mounting Box for Outdoor Bell FFS06431510 |
|  ESI-40, Red Weatherproof Open-Area Sounder, 100 dBA FFS06728040 |  ESI-80, Loop Powered Beacon without Base FFS06728080 |  C-C Ceiling Visual Alarm Device 15m Red, Loop Powered FFS06728124 |  MBF-6EV, Fire Bell Indoor FFS06431065 |
|  Red Cap For Base Sounder FFS06728091 and White Cap FFS06728092 |  EBI-12, Mouting Base Deep FFS06720012 |  C-C Wall Visual Alarm Device 6m Red, Loop Powered FFS06728125 | |



Switch In

-  EME210-I, Input Unit with Isolator - Surface Mounted FFS06727311

I/O Module

-  EME212-I, Input/Output Unit with Isolator - Surface Mounted FFS06727312


Manual Call Point

-  ECE221-I, Manual Call Point, with Isolator, Red, Resettable FFS06720318
-  Manual Call Point IP67, with Isolator FFS06723736









EX Zone

- | | |
|--|---|
|  Optical Smoke Detector IS, XP-95 FFS06725227 |  Single Channel Protocol Translator FFS06725201 |
|  Heat Detector (A2S) IS, XP-95 FFS06725257 |  Galvanic Isolator FFS06725203 |
|  Mounting Base IS FFS06725207 |  Manual Call Point IS, XP-95 FFS06723737 |









Aspiration

-  ASD531 1S with Sensor FFS06432669
-  ASD532 1S with Smoke Level Indicator FFS06432670
SSD532 Smoke Sensor FFS06432673
-  ASD535-3 1S AD Display FFS06432543
-  ASD535-4 2S AD Display FFS06432544
-  SSD535-3 Smoke Sensor High Sensitivity FFS06432547
-  FBS 25 PC Filter Box Small FFS06432551

Detection without standard

- | | |
|--|---|
|  EBI-50, Addressable Duct Detector Housing FFS06720050 |  Intellia UV Flame Detector FFS06725283 |
|  EST-10, Duct Detector Longer tube 150-750mm FFS06720051 |  Intellia IR2 Flame Detector FFS06725284 |
|  EDI-60, CO Detector FFS06720260 |  Intellia IR3 Flame Detector FFS06725285 |
|  HEAT DETECTION CABLE |  EBI-12, Mouting Base Deep FFS06720012 |

Wireless

- | | |
|---|--|
|  XPA-IN-14050-APO, Loop Interface Wless Communication FFS06726036 |  XPA-CB-14001-APO, Wless Red Sounder with Base FFS06726007 |
|  XPA-CB-12034-APO, Wless Optical Detector with Base FFS06726002 |  XPA-CB-14003-APO, Wless Red Sounder Beacon with Base FFS06726009 |
|  XPA-CB-11171-APO, Wless CS Heat Detector with Base 90C FFS06726005 |  XPA-IN-14011-APO, Wless IO Unit Single Channel FFS06726024 |
|  XPA-CB-11170-APO, Wless A1R Heat Detector with Base 57C FFS06726004 | |
|  XPA-MC-14006-APO, Wless Manual Call Point FFS06726006 | |